



Zhuhai HiVi Technology Company Limited

Add.: No. 1, South Dongcheng Road, Liangang Industrial Zone, Jinwan District ,Zhuhai City, Guangdong Province, 519045, P. R. China

Tel: +86-756-6268133

Fax: +86-756-6268068

e-mail: sales.zs@hivi.com

Model

E6.5N
mid-bass speaker



Product Parameterit

| | |
|-----------------------|----------------------------|
| Rated Impedance | 8Ω |
| Resonance Frequency | 43Hz |
| Rated Power | 60W |
| Peak Power | 120W |
| Sensitivity(2.83V/1m) | 88dB |
| Weight | 1.78kg |
| Voice Coilce | |
| Diameter | 25mm |
| DC Resistance | 6.5Ω |
| Width | 14.5mm |
| Voice coil wire | High temperature SV wire |
| Voice coil bobbin | AL |
| Magnetic Circuit | |
| Magnetic circuit type | Dual magnetic antimagnetic |
| Material | High Performance Ferrite |
| BL Value | 7.14N/A |
| Magnetic gap height | 6mm |
| Xmax | 4.25mm |
| Small/Thiele | |
| Compliance | 894.9uM/N |
| QMS | 1.96 |
| QES | 0.51 |
| Qts | 0.4 |
| Mms | 14.7g |
| Equivalent volume | 21L |
| Recommend Cabinet | |
| Type | Phase Inverted |
| Vb | 16.2L |
| FB | 51Hz |
| F3 | 48Hz |

