

**FEATURES**

- Heavy-duty design with a 32 mm voice coil for a high 20 watt RMS power handling
- Pre-applied 3M™ VHB™ adhesive for quick, secure installation
- Rare-earth neodymium motor and a proprietary two-layer voice coil
- 4 ohms impedance for use with small, Class D amplifiers


**APPLICATIONS**

- Invisible home theater and multi-room audio
- Electronic gaming machines
- Advertising signage
- Point-of-purchase displays
- Multimedia exhibits
- Commercial distributed audio
- Kiosks
- Automotive audio
- Bathroom tubs and showers

**PARAMETERS**


Impedance	4 ohms
Re	3.5 ohms
Le	0.23 mH @ 1 kHz
Fs	160 Hz
Qms	N/A
Qes	N/A
Qts	N/A
Mms	N/A
Cms	N/A
Sd	N/A
Vd	N/A
BL	N/A
Vas	N/A
Xmax	N/A
VC Diameter	32 mm
SPL	N/A
RMS Power Handling	20 watts
Usable Frequency Range (Hz)	N/A

**IMPEDANCE/PHASE**



Measurement taken with transducer uncoupled facing upward.

**FREQUENCY RESPONSE**



OMNIMIC

OmniMic

1/3<sup>rd</sup> octave smoothing - measurement taken with transducer adhered off-center on a 12" x 12" x 1/2" foam core board in an infinite baffle setup.

Note: This information is for comparison purposes only, the actual frequency response will depend on many factors of which the diaphragm being the greatest contributor.