

# Active Pro Monitor

## APM-4200 Active stage monitor plate amp

High-definition audio quality with finely tuned crossover and efficient class-D amplification.

Refined tonal quality due to best-in-class class D topology. 1000 Watt Peak power - 420 Watt RMS.

Suitable for 15" Woofers (350w) and 70w HF 40 Hz to 20 k Hz frequency response.

### High Power 2-way

- Short-circuit/overload/high frequency output protections
  - Clip limiter, permanent signal limiter • Output for passive speaker
  - Line out for Active speaker
  - THD under 1% at RMS
  - Efficiency and robustness, always and everywhere
  - Maximize performances. minimize consumption.
- Separate gain control of LF and HF to tune as per end use requirement



## Specification:

MODEL	APM - 4200
Configuration	2 Way
Frequency Response	20Hz-20kHz±1dB
Power Supply	220v/50-60Hz
S/N rate 1kHz	>100dB
Technology	Class G
Input signal:	bal/unbal
Input/ Output connectors	XLR
Input sensitivity	0.77V
Wattage	400+100 watt
Protections:	Thermal,DC Protection
Limiter:	Soft Limiter
Cooling:	Forced Fan
Channel separation 1kHz	>80dB
Product Dimensions(mm)	170x250x120
Product Gross Weight	5kg